



■ DW 3x9 PRO 150 KG



CERTIFICATE
EN 131
PROFESSIONAL USE



DW 3 150 KG - PRO

INDUSTRIAL ALUMINUM LADDER

- Professional **three-element ladder** PRO is a perfect work tool for specialists looking for the highest standards of safety and durability
- Stabilizer** mounted only with screws!
- Rungs with a **28x28 [mm]** profile have **grooves**, attached to the profile with a strong pressing system
- Possibility of using the ladder on stairs!* (See page 69)
- Clamp-on anti-slip feet
- The guides makes it easy to set the ladder in a free-standing position
- Solid hooks, guiding profile elements and automatic locks
- Load capacity **max. 150 kg**
- Quality **EN 131**
- Certified by **TÜV Rheinland**

DW 3 150 KG		NUMBER OF RUNGS	3x6	3x7	3x8	3x9	3x10	3x11	3x12	3x13	3x14	3x15	3x16
	A1 [m] WORKING HEIGHT		3,40	3,75	4,00	4,51	5,01	5,01	6,04	6,56	7,06	7,58	8,08
	A2 [m] WORKING HEIGHT		4,43	5,05	5,05	5,83	6,31	6,31	8,09	8,61	9,62	10,39	10,83
	B1 [m] LADDER LENGTH		1,68	1,95	2,20	2,46	2,72	2,98	3,25	3,52	3,78	4,05	4,31
	B2 [m] LADDER LENGTH		3,45	4,09	4,09	4,90	5,39	5,39	7,24	7,77	8,82	9,62	10,07
	C [m] LADDER WIDTH		0,45	0,45	0,45	0,45	0,45	0,45	0,48	0,48	0,48	0,48	0,48
	G [m] LADDER THICKNESS		0,155	0,155	0,155	0,16	0,175	0,175	0,19	0,19	0,22	0,22	0,22
	WEIGHT [kg]		9,10	10,20	11,50	13,00	15,10	16,40	23,00	24,60	30,00	32,00	34,00